

lot innebygd PC-faneløs, jernbane godkjent, -40°C til 70°C RS232 / 422/485, USB, Triple Display Support, 9 ~ 48VDC

Product price:

kr 0.00 tax excluded

Product features:

CPU: Onboard 8th Intel® Core™ U Processors (Whiskey Lake) Intel® Core™ i7/i5 Quad Core, i3 Dual Core Processor 15W

Annex: Expansion: 1x High Speed CMI Interface for optional CMI Module Expansion 1x Low Speed CMI Interface for optional CMI Module Expansion 1x CFM IGN Interface for optional CFM-IGN Module Expansion

BIOS: AMI BIOS

Approval: EMC CE, FCC, ICES-003 Class A, EN50121-3-2 (Railway), E-mark Safety IEC/EN 62368-1

Beskyttelse: Over Voltage Protection Protection Range: 51~58V Protection Type: shut down operating voltage, re-power on at the preset level to recover Over Current Protection 15A Surge Protection 3.84 kV (impedance 12 ohm 1.2/50us waveform)

Chok/Vibration: SHOCK MIL-STD-810G

Vibration MIL-STD-810G

Dimensioner: 203x142x66.8mm

Driftstemperatur: • -40°C to 70°C PassMark

Burn-In Test: 100% CPU, 2D/3D Graphics (without thermal throttling) With extended temperature peripherals; Ambient with air flow According to IEC60068-2-1, IEC60068-2-2, IEC60068-2-14

Ethernet: 2x GbE LAN RJ45, GbE1 Intel I219, GbE2 Intel I210

Forsyning: 9~48VDC via 3-pin Terminal Block Grafik: Graphics Engine Integrated Intel® UHD Graphics 620

Hukommelse: 1 x DDR4 SO-DIMM socket, max. 64GB up to 2400MHz (un-buffered and non ECC)
Køling: 1x External FAN Connector, 4-pin Terminal Block (Support Smart Fan by BIOS)
Lyd: Realtek ALC 888 HDA, line in/out jack 3.5mm
Montering: OPTION! WALL/SIDE/DIN-RAIL/VESA Mount
Msata: 1x mSATA socket (SATA 3.0 shared by mini PCIe Socket)
OS SUPPORT: Windows 10/11
Porte: 2x RS-232/422/485 with Auto Flow Control (Supports 5V/12V), DB9
RAID niveau: SUPPORT RAID 0/1
SIM kort: 2x SIM Socket
Udgange: Supports Triple Independent Display HDM (4096 x 2304@60Hz) DP (4096 x 2304@60Hz) VGA(1920 x 1200 @60Hz)
USB: 2x 3.2 Gen2, Type A 2x 3.2 Gen1, Type A 2x 2.0, Type A
Vekt: 2.74Kg
Watchdog: Software Programmable Supports 256 Levels System Reset

Product attributes:

Product codes:

Reference: EPC-IXGEN8C-2E2C6U
EAN13: -
UPC: 20666

Product short description:

Embedded 8th Gen Intel® Core™ U I7 / I5 / I3 CPU (TDP 15W)
1x 2.5 "Front Tilgjengelig SATA HDD Bay for rask tilgang og 1x MSATA Socket
2x Full-size Mini PCIe-stikkontakter For Modul Expansion
2x Front Tilgjengelige SIM-kortspor for Signal Redundans
Valgfrie CMI-moduler (2x 10 GBE LAN, M12 A-kodet eller M12 X-kodet)
Valgfrie CFM-moduler (Power Tenning Sensing, eller 4x PoE)
Bred driftstemperatur -40 ° C til 70 ° C
203 mm (W) x 142 mm (D) x 66.8 mm (H)
MIL-STD-810G, E-Mark, og EN50155 (kun EN 50121-3-2) Sertifisert
9~48VDC via 3-pin Terminal Block

